


ADA 0 58156





Report 2239

TRACTOR, WHEELED, WAREHOUSE, GASOLINE, 4000-POUND-DRAWBAR-PULL, PNEUMATIC-TIRE -MANUFACTURER SURVEY

by

James E. Stephens, Jr.

and

Jesse W. Reid, Jr.

March 1978

Approved for public release; distribution unlimited.

U.S. ARMY MOBILITY EQUIPMENT RESEARCH AND DEVELOPMENT COMMAND FORT BELVOIR, VIRGINIA

78 08 30 028

Destroy this report when it is no longer needed. Do not return it to the originator.

The citation in this report of trade names of commercially available products does not constitute official endorsement or approval of the use of such products.

14 MERADCOM-2239

UNCLASSIFIED

	REPORT DOCUMENTATION	PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
	1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
	2239		5. TYPE OF REPORT & PERIOD COVERED
6	TRACTOR, WHEELED, WAREHOUSE, C	GASOLINE,	S. THE OF REPORT & PERIOD COVERED
7	4000-POUND-DRAWBAR-PULL, PNEUM	ATIC-TIRE -	6. PERFORMING ORG. REPORT NUMBER
V	MANUFACTURER SURVEY	*)	4. PERFORMING ONG. REPORT NUMBER
	James E. Stephens, Jr.		8. CONTRACT OR GRANT NUMBER(*)
0	Jesse W./Reid, Jr.		
\leq	9. PERFORMING ORGANIZATION NAME AND ADDRESS		10. PROGRAM ELEMENT PROJECT TASK
	Mechanical and Construction Equip Lab, I US Army Mobility Equipment Research an Command, Fort Belvoir, Virginia 22060	ORDME-HM nd Development	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
	11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE
	Commander US Army Mobility Equipment Research as	nd Development	Mar 178
	Command, Fort Belvoir, Virginia 22060	nd Development	34 (12) 30b.)
	14. MONITORING AGENCY NAME & ADDRESS(If different	from Controlling Office)	15. SECURITY CLASS. (of the
			UNCLASSIFIED
			15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
	16. DISTRIBUTION STATEMENT (of this Report)		
	Approved for public release; distribution to	ınlimited	
	Approved for public felease, distribution of	inimired.	
	17. DISTRIBUTION STATEMENT (of the abstract entered in	in Block 20, if different from	n Report)
	18. SUPPLEMENTARY NOTES		
	19. KEY WORDS (Continue on reverse side if necessary and Material-Handling Equipment Reliabil	d Identify by block number) lity, Availability, and	Maintainability
	Warehouse Tractor Quality	Assurance	
	Gasoline Engine Specific Pneumatic Tire Procure		
	Maintenance	·	
_	This report is the result of emphasis o		cial warehouse tractors in lieu of
	Military Adaptation of Commercial Items fielding commercial material-handling equiprogram. This report presents the results	s (MACI). To satisfy uipment, MERADC	the prerequisites for procuring/ OM implemented a seven-phase
	(Cor	ntinued)	
	403160	X	
	403160)	Some

DD 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED


SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

(Block 20 (Cont'd))

Four manufacturers of warehouse tractors were visited by a Survey Team using a Manufacturer Survey Questionnaire (Technical Information Package (TIP)). Each manufacturer proposed a model which should satisfy the item description used in conjunction with the TIP.

Results from the survey include a candidate make and model list for commercial warehouse tractors. The results also support this general conclusion: Commercial warehouse tractors do not differ significantly from warehouse tractors previously procured by the Army using MACI specifications.





CONTENTS

Section	Title	Page
	ILLUSTRATIONS	iv
	TABLES	iv
	METRIC CONVERSION FACTORS	v
I	INTRODUCTION	
	1. Background	1
	2. Objective	1
	3. Description of Warehouse Tractor	1
	4. Scope	3
II	SURVEY OF MANUFACTURERS	
	5. Baseline Description of Warehouse Tractor	3
	6. Preparation of the Manufacturer Survey Questionnaire	3
	7. Selection of Manufacturers	
Ш	RESULTS OF SURVEY OF MANUFACTURERS	
	8. Visits to Manufacturers	4
	9. TIP Evaluation	4
IV	CONCLUSIONS	
	10. Conclusions	21
	APPENDIX – Item Description for Tractor, Wheeled, Warehouse, Gasoline, 4000-Pound-Drawbar-Pull, Pneumatic	22

ILLUSTRATIONS

Figure	Title	Page
1	Warehouse Tractor Purchased via MIL-T-52852	2
2	Northwestern J6-40-PT15 Warehouse Tractor	6
3	United Shop Mule SM-40 Warehouse Tractor	7
4	Clark CT-40 Warehouse Tractor	8
5	Pettibone Huskie Model 40 Warehouse Tractor	9

TABLES

Number	Title	Page
1	Comparison of Commercial Warehouse Tractors vs Existing	10
	Specifications	
2	Comparison of Technical/Automotive Characteristics of	14

METRIC CONVERSION FACTORS

Approximate Conversions to Metric Measures

Symbol	When You Know	Multiply by	To Find	Symbol
	<u>-</u>	LENGTH		
	inches	*2.5	centimeters	cm
in ft	feet	30	centimeters	cm
vd	vards	0.9	meters	m
mi	miles	1.6	kilometers	km
		AREA		
in ²	square inches	6.5	square centimeters	cm ²
ft ²	square feet	0.09	square meters	m ²
ft ² yd ² mi ²	square yards	0.8	square meters	m ²
mi ²	square miles	2.6	square kilometers	km ²
	acres	0.4	hectares	ha
		ASS (weight)		
oz	ounces	28	grams	g
lb	pounds	0.45	kilograms	kg
	short tons (2000 lb)	0.9	metric tons	t
		VOLUME		
tsp	teaspoons	5	milliliters	mt
Tbsp	tablespoons	15	milliliters	mi
fl oz	fluid ounces	30	milliliters	ml
С	cups	0.24	liters	L
pt	pints	0.47	liters	L
qt	quarts	0.95	liters	L
gal	gallons	3.8	liters	L,
ft ³	cubic feet	0.03	cubic meters	m ³
yd ³	cubic yards	0.76	cubic meters	m ³
	TEMP	ERATURE (exact)		
°F	Fahrenheit	5/9 (after	Celsius	С
	temperature	subtracting 32)	temperature	

^{• 1} in = 2.54 cm (exactly).

Symbol Symbol	When You Know	Multiply by	To Find	Symbo
	WHEN YOU KNOW	multiply by	10 Find	Symbo
		LENGTH		
		LENGTH	_	
mm	millimeters	0.04	inches	in
cm cm	centimeters	0.4	inches	ir
m	meters	3.3	feet	ft
8 m	meters	1.1	yards	ye
km ,	kilometers	0.6	miles	m
		AREA		
cm ²	square centimeters	0.16	square inches	in ²
m ²	square meters	1.2	square yards	yd mi
km ²	square kilometers	0.4	square miles	mi ²
ha	hectares (10 000 m ²) 2.5	acres	
		MASS (weight)		
g	grams	0.035	ounces	02
kg	kilograms	2.2	pounds	lb
t	metric tons (1000 kg)	1.1	short tons	
		VOLUME		
		AOLOME		
ml	milliliters	0.03	fluid ounces	fl oz
L	liters	2.1	pints	pt
ĭ	liters	1.06	quarts	qt
L	liters	0.26	gallons	gal
m ³	cubic meters	35	cubic feet	ft ³
m ³	cubic meters	1.3	cubic yards	yd ³
	TEM	PERATURE (exac	<u>t)</u>	
°C	Celsius	9/5 (then	Fahrenheit	0
	temperature	add 32)	temperature	
			op	
	°F 32	98.6	21	2
	40 0 40	80 120	160 200	
		20 40 37		

TRACTOR, WHEELED, WAREHOUSE, GASOLINE, 4000-POUND-DRAWBAR-PULL, PNEUMATIC-TIRE – MANUFACTURER SURVEY

I. INTRODUCTION

- 1. Background. On 24 May 1976, the Office of Management and Budget directed the Government to emphasize the acquisition of commercial, off-the-shelf products in order to achieve optimal effectiveness in supply support operations. The resulting emphasis on procurement of commercial products included the warehouse tractor. Therefore, MERADCOM initiated a program to develop a procurement whereby commercial, off-the-shelf warehouse tractors could be procured and supported. An outline of this program for the warehouse tractor included the following elements:
 - a. Prepare the Manufacturer Survey Questionnaire.
 - b. Conduct and report the Manufacturers Survey.
 - c. Prepare the User Survey Questionnaire.
 - d. Conduct and report the Users Survey.
 - e. Develop the procurement specification.
 - f. Procure commercial warehouse tractors.
 - g. Type classify.
- 2. Objective. This report presents the results of a survey of four manufacturers of commercial warehouse tractors: Clark, Northwestern, Pettibone, and United.
- 3. Descriptions of Warehouse Tractor. Heretofore, Military adaptations of commercial warehouse tractors have been procured using Military Specification MIL-T-52852 (a tow tractor procured using MIL-T-52852 is shown in Figure 1). This specification, in turn, was assumed to represent the requirement baseline for commercially available warehouse tractors. These commercial warehouse tractors can be described as follows:

Characteristic	Requirement
Drawbar pull	4000 lb (minimum)
Engine type	Gasoline
Transmission	Automatic
Number of speeds forward	2 (minimum)




Figure 1. Warehouse tractor purchased via MIL-T-52852

Number of speeds rearward

1

Speed

12 mi/h (minimum)

Tires: Number

4

Type

Pneumatic

Maneuverability

 90° turns from and into intersecting 90-

inch-wide aisles.

Temperature range in which vehicle

0° to 110° F

must operate

Typical use

In general warehouses and depots pulling trailer trains, and at airfields towing aircraft.

4. Scope. This report considers this program's two initial elements:

a. Preparing the Manufacturer Survey Questionnaire.

b. Conducting and reporting the Manufacturer Survey.

II. SURVEY OF MANUFACTURERS

- 5. Baseline Description of Warehouse Tractor. The manufacturer questionnaire was designed as a "dry run" of the first step of two-step procurement. Therefore, a baseline description was necessary to ensure that each manufacturer would respond to the identical baseline. The warehouse tractor description presented in paragraph 3 was expanded into a narrative format to include the Army's requirements and to encompass commercially available warehouse tractors. This description is presented in the Appendix to this report.
- 6. Preparation of the Manufacturer Survey Questionnaire. MERADCOM developed a survey questionnaire for use in the Commercial Equipment Program and for eventual use in two-step procurement of warehouse tractors. As the first procurement step, the manufacturer uses the questionnaire to describe his product. The Government then evaluates the manufacturer's response to ensure that it represents the manufacturer's commercial product and satisfies the Contract Specification. Part of the Government's evaluation includes input from a survey of commercial users of these warehouse tractors. The manufacturers judged to be responsive are then requested, as the second procurement step, to submit competitive bids on their response/descriptions. Finally, the Government uses the information presented by the manufacturers in step one to accept or reject the warehouse tractors when they are inspected for acceptance by the Government.

The Manufacturer Survey Questionnaire was coordinated with interested agencies including TARCOM and DARCOM Packaging, Storage, and Containerization Center (User Representative). The questionnaire was developed to solicit the following from the manufacturer:

- a. Candidate model.
- b. Standard equipment list.
- c. Optional equipment list.
- d. Major component specification/manufacturer/part number.
- e. Logistical/maintenance data.
- f. Commercial user list.

The resulting questionnaire was designated the Technical Information Package (TIP) for the warehouse tractor. Each manufacturer was requested to complete the TIP for his tow tractor which corresponds to the previously discussed item description.

7. Selection of the Manufacturers. The following criteria were developed to identify manufacturers of tow tractors which match the Army's requirements: "The manufacturer shall produce a standard warehouse tractor which corresponds to the item description. Furthermore, the manufacturer shall have marketed the standard tractor in significant quantities to the Government and/or commercial users for at least 1 year. However, the introduction of normal product improvement changes in this 1-year period is acceptable." These criteria, except for one change, are similar to those used in other Commercial Equipment Programs. "Supplying warehouse tractors to the Government" was added as a qualifier; otherwise, two manufacturers, Northwestern and United, would have been excluded because their commercial markets are relatively small. Four U.S. manufacturers (Clark, Pettibone, United, and Northwestern) were identified as survey candidates whose tractors met these criteria.

III. RESULTS OF SURVEY OF MANUFACTURERS

- 8. Visits to Manufacturers. The four manufacturers of commercial warehouse tractors identified above were visited by a survey team composed of a member from MERADCOM and TARCOM's Quality Assurance and Maintenance Directorates. The survey team explained the Commercial Equipment Program and stressed the point that commercial warehouse tractors would be procured only if they satisfied the Army's requirement. Each manufacturer was cooperative and fulfilled MERADCOM's request to submit a completed TIP to MERADCOM.
- 9. TIP Evaluation. Prior to a discussion of the results contained in the Technical Information Packages, it is appropriate to present the findings of the visits to the manufacturers. The manufacturers were equally divided for and against endorsing the

Commercial Equipment Program concept. All manufacturers use Quality Assurance Procedures which satisfy the requirements of Military Specification MIL-I-45208. Each manufacturer provided a maintenance manual to the survey team member from TARCOM Maintenance Directorate. Commercial Logistical Support and Warranties were discussed. Three manufacturers provide logistical support and warranty service through their local dealer networks and the other manufacturer provides these services direct from the factory. Finally, the pros and cons of delivery through the local dealer to the Government user were discussed. Two problems were identified; The dealer is unfamiliar with the Government Procurement System, and the dealer has no incentive to provide service unless he shares the profits of sale or of future sales. However, one manufacturer was in favor of delivery of tractors through his local dealers, since the manufacturer would be assured of proper pre-service before the tractor is put in service. This assurance of proper dealer preparation would eliminate many warranty problems which in the past have been traced to improper setup by the Government user.

- a. The following warehouse tractors were depicted by the corresponding manufacturers in the TIPs submitted to MERADCOM: Clark, CT-40; Northwestern, J6-40-PT15; Pettibone, Huskie Model 40; and United Shop Mule SM-40. Photographs of these tractors are shown in Figures 2 through 5.
- b. Table 1 was prepared from the data presented in each TIP to compare the various standard, optional, and non-standard features of each tractor and to compare each tractor to MIL-T-52852 for reference purposes. In general, the comparison verifies a pre-survey observation: Warehouse tractors purchased via MIL-T-52852 are not significantly different from commercial warehouse tractors. All of the requirements of MIL-T-52852 can be satisfied by either optional or available features from each manufacturer. Table 1 will be used to develop the rationale concerning which features should be specified in the "new" specification. One approach would be to specify only those desirable features not standard with all manufacturers. Front brakes, as an example, are not standard and should be specified in the new specification. This approach assumes the manufacturer would provide his standard model for the "new" specification.
- c. Table 2 compares the technical/automotive characteristics of commercial tow tractors from the four manufacturers surveyed. Technically/automotively the tractors do not differ significantly from tow tractors previously procured using MIL-T-52852 except for certain features such as the absence of front brakes on the United tractor or the non-conformance of Pettibone's seat with SAE J899.



Figure 2. Northwestern J6-40-PT15 warehouse tractor.



Figure 3. United Shop Mule SM-40 warehouse tractor.



Figure 4. Clark CT 40 warehouse tractor.




Figure 5. Pettibone Huskie Model 40 warehouse tractor.

Table 1. Comparison of Commercial Warehouse Tractors vs Existing Specifications

LEGEND: S = Standard, furnished. O = Optional. N = Not Standard, not furnished (may be option). SF = Special Feature (may be option).

Feature		Manufacturer	turer		Requirement of MIL-T-52852
	Northwestern	United	Pettibone	Clark	(Par. No.)
Gasoline Engine	S	S	S	S	1.1
LPG Engine	0	0	0	0	
Diesel Engine	0	0	0	0	
Crankcase Ventilation System	S	S	S	S	3.9.2.10
Pressurized Cooling System	S	S	S	s	3.9.2.5.4
Governed Engine Speed	S	S	S	s	3.9.2.6
Governor	S	S	S	s	3.9.2.6
Air Cleaner Restriction Indicator	S	SF	0	SF	3.9.2.4.2
Fuel Pump - ANSI B56.4	S	S	S	S	3.5
Fuel Filter	S	S	S	S	3.9.2.4
Carburetor – ANSI B56.4	S	S	S	S	3.5
Water Pump	S	S	S.	S	3.9.2.5.2
Thermostat	S	S	S	S	3.9.2.5.3
Alternator	S	S	S	s	3.9.2.2
Full Flow Oil Filter	S	S	S	S	3.9.2.8
Battery - SAE J537	S	z	S	S	3.24.2
Battery Hold-Downs	S	S	S	S	3.24.4.1
Battery Inclosure Acid-Resistant	S	S	S	Z	3.24.4.1
Alternator-Waterproofing	0	Z	Z	z	3.9.2.9
Alternator-Fungusproofing	0	Z	S	Z	3.9.2.9
Alternator Protection Rev. Polarity	0	Z	0	Z	3.9.2.2.1
Voltage Regulator	S	S	S	S	
Starter Motor-Fungusproofing	0	Z	Z	z	3.9.2.9
Fan-Viscous Drive	Z	Z	Z	Z	
Fuel Tank-ANSI B56.4	S	S	S	S	3.5
Lead-Free Gasoline	S	Z	s	S	

Table 1. Comparison of Commercial Warehouse Tractors vs Existing Specifications (Cont'd)

Feature		Manufacturer	turer		Requirement of MIL-T-52852
	Northwestern	United	Pettibone	Clark	(Par. No.)
Torque Converter	S	S	S	S	3.10
Automatic Transmission	S	S	S	S	3.10
Transmission Filter - Internal Screen	S	S	S	Z	3.10.1
Front Axle - Suspension	S	S	S	s	3.15
Front Axle – 2 Tires	S	S	S	S	3.13
Rear Axle Suspension	S	Z	S	S	3.15
Rear Axle – 2 Tires	S	Z	S	S	3.13
Steering System - Manual/Power	S	S	S	S	3.14
Front Brakes	S	Z	S	s	3.16.1
Front Brakes - Manual Adjustment	S	Z	S	S	3.16.1
Front Brakes - Self-Adjusting	Z	z	Z	Z	3.16.1
Front Brakes - Power-Assisted	Z	Z	S	S	3.16.1
Front Brakes - Hydraulic-Actuation	S	Z	Z	Z	3.16.1
Rear Brakes	S	S	S	S	3.16.1
1	S	S	Z	s	3.16.1
Rear Brakes — Self-Adjusting	Z	z	S	z	3.16.1
Rear Brakes - Power-Assisted	Z	Z	S	S	3.16.1
Rear Brakes - Hydraulic-Actuation	S	S	Z	Z	3.16.1
Parking Brake	S	S	S	S	3.16.2
Seat – SAE J899	S	S	Z	S	3.18
Vehicle Noise Level – 85dB (A)	S	Z	S	S	3.25.6
Alternator Indicator Light	Z	0	0	SF	3.23.8
Ammeter	S	S	S	S	3.23.1
Voltmeter	Z	SF	0	SF	
Engine Hourmeter	S	S	S	S	3.23.12
Engine Oil Pressure Gauge	S	S	S	S	3.23.9
Engine Oil Low-Pressure Warning Light	z	0	0	SF	3.23.9
Engine Coolant Temperature Gauge	S	S	s	S	3.23.10
Engine Coolant High-Temperature Warning Light	z	0	0	SF	3.23.10
Transmission Oil Temperature Gauge	S	S	0	SF	3.23.11

Table 1. Comparison of Commercial Warehouse Tractors vs Existing Specifications (Cont'd)

	The second secon				
					Requirement of
Feature		Manufacturer	turer		MIL-T-52852
	Northwestern	United	Pettibone	Clark	(Par. No.)
Transmission Oil High-Temperature Warning Light	Z	0	0	SF	3.23.11.
Fuel Gauge	S	S	S	S	3.23.13
Air Cleaner Restriction Indicator	S	SF	0	SF	3.9.2.4.2
Key Ignition Switch	S	S	S	S	3.2.3.3
12-Volt Electrical System	S	S	S	S	3.24.4
Instrument Panel Lights	S	0	0	SF	
Individual Light Switches	Z	0	0	S	
Directional Signals	0	0	0	SF	
Flashing Warning Lights	0	0	0	SF	
Front Travel Lights - Two	S	S	0	S	3.24.1
Front Flood Lights	Z	0	0	SF	
Rear Backup Light – One	S	0	0	S	3.24.3
Electrical Circuit Breakers	Z	0	0	SF	3.24
Electrical Fuses	S	S	S	S	3.24
Radiator Guard	S	S	S	S	3.9.2.5.4
Spark-Arresting Muffler	S	s	0	SF	3.5
Seat Belt	0	0	0	SF	
Horn	S	S	S	S	3.24.5
Protecto Seal Fuel Filter	S	S	S	S	3.9.2.4
Fire Extinguisher	0	0	0	SF	
Closed Cab	0	0	0	0	3.21
Neutral-Start Protective Switch	S	S	S	S	3.9.2.3
Starter Protective Switch — After Engine Start	S	0	S	S	3.9.2.3
Spring-Counterbalanced Hood	S	0	Z	S	3.19
Positive Hood Hold-Open Device	0	S	S	SF	3.19
Windshield Wipers — Two	0	0	0	0	3.21
Cab Heater	0	0	0	0	3.21
Cab Defroster	0	0	0	0	3.21
Noise Control Provisions	Z	0	0	Z	
Screw Threads – NBS H28	S	S	S	S	3.7.3

Table 1. Comparison of Commercial Warehouse Tractors vs Existing Specifications (Cont'd)

Feature		Manufacturer	turer		Requirement of MIL-T-52852
	Northwestern	United	Pettibone	Clark	(Par. No.)
Lubrication Fittings – SAE J534	S	S	S	S	3.7.2.2
Engine/Transmission Elastomer Shock Mounts	S	S	S	S	3.10.4
Identification/Warning Plates	S	S	S	S	3.28
Color End Item – Yellow	S	S	S	S	3.26
Non-Slip Walkway Coating	S	S	S	SF	3.26.1
Warranty Furnished	S	S	S	S	
Operator's Manual Furnished	S	S	S	S	
Maintenance Manual Furnished	S	S	S	S	
Rebuild Manual Furnished	S	S	z	0	
Repair Parts Manual Furnished	S	S	S	S	
Lubrication Instructions Furnished	S	S	S	S	
Training Aids Furnished	Z	Z	Z	0	
Revisions to Manuals After Issue	S	S	S	Z	
Tiedown Provisions Provided	S	S	z	Z	3.22
Lifting Provisions Provided	S	S	z	Z	3.22
Choke - Automatic or Manual	s	S	S	S	3.9.2.1
Transmission Control - Right-Hand Operation	S	S	S	S	3.23.7
Speed (FWD) – 12 mi/h/min	S	S	S	S	3.2.5.3
Speed (REV) - NLT 5 mi/h	S	S	S	S	3.2.5.3
EMI – SAE JS51a	*	*	S	*	3.27
Coupler	S	S	S	S	3.12
Operate for 6 hours w/o refilling fuel	S	S	S	S	1
4 Wheel Brakes	S	Z	S	S	3.16.1

^{*} Question not asked on questionnaire before being revised.

Table 2. Comparison of Technical/Automotive Characteristics of Four Commercial Warehouse Tractors

Specifications	Northwestern Model J6-40PT15	United Model Shop Mule SM40	Pettibone Model Huskie Model 40	Clark Model CT 40
	Engine and Er	Engine and Engine Accessories		
Engine manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Number of cylinders	9	9	9	9
Bore (in.)	3.41	3.4	4.00	4.00
Stroke (in.)	4.12	4.125	3.98	3.98
Total displacement (in.3)	225	225	300	300
Compression ratio	8.2:1	8.4:1	8.4:1	7.9:1
Gross horsepower @ r/min	Not stated	132 (4 4000	149 @ 2800	132 @ 3600
Intermittent horsepower (a r/min	95 @ 3600	100 (a 3600	119 @ 2800	132 @ 3600
Continuous horsepower (a r/min	70 @ 3200	79 (4) 3200	101 @ 2800	102.5 @ 2800
Max. governed horsepower (a r/min	95 @ 2500	105 (4 2800	115 @ 2650	86 @ 2600
Net horsepower (a r/min	120 @ 4000	120 @ 4000	115 @ 2650	Not stated
Max. torque (lb/ft) @ r/min	195 (a 2000	196 (a 1200	249 @ 1600	241 @ 1800
Engine conform to Calif. Title B	Not stated	No	No	No
Governed engine speed (no-load) at r/min	2400	2800	2600-2650	2650
Governor manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Air cleaner manufacturer	Chrysler	Chrysler	Ford Motor Co.	Donalson
Restriction indicator	No	No	No	No
Mounting location	N/A	N/A	N/A	N/A
Type of hose clamps	Not stated	Not stated	Worm gear-band type	Adj. Strap
Fuel pump manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Conform to ANSI B56.4	Yes	Yes	Yes	Not stated
Fuel filter manufacturer	Chrysler	Chrsyler	Ford Motor Co.	Ford Motor Co.
Location	In fuel line	In fuel line	Part of eng. fuel pump	Top of pump
Carburetor manufacturer	Chrysler	Carter	Ford Motor Co.	Ford Motor Co.
Type	Downdraft	Downdraft	Downdraft	Downdraft
Conform to ANSI B56.4	Yes	Yes	Yes	Yes
Choke actuation	Manual	Automatic	Manual	Manual
Crankcase ventilation system manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Type	Positive	Vent. valve filament	Positive	Positive
Spark plugs manufacturer	Champion	Champion	Ford Motor Co.	Autolite
Ignition wires manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Resistance/foot (rated)	Not stated	Not stated	50 ohms	Not stated
Distributor manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.

Table 2. Comparison of Technical/Automotive Characteristics of Four Commercial Warehouse Tractors (Cont'd)

Specifications	Northwestern Model J6-40PT15	United Model Shop Mule SM40	Pettibone Model Huskie Model 40	Clark Model CT 40
Type	Electronic	Centrifugal	Breaker PT-Condenser	Contact Point
Ignition coil manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Muffler manufacturer	Nelson	Nelson	Nelson	Nelson
Type	Baffled-single pass	Spark-arresting		Tuned multi-pass
Conform to ANSI B56.4	Yes	Yes	Yes	Yes
Cooling system	Liquid pressurized	Liquid pressurized	Liquid pressurized	Liquid pressurized
Capacity (US gal)	3.25	5.5	4.5	3.75
Pressure (operating) (lb/in ²)	14	7	7	7
Type of antifreeze furnished	Ethylene glycol	Ethylene glycol	Ethylene glycol	Ethylene glycol
Radiator manufacturer	Chrysler	Young	Southern Radiator Co.	McCord (Young)
Capacity (qt)	13	14.5	16	16
Radiator construction	Fin & tube, vertical	Fin & tube	Fin & tube	Fin & tube
	flow			
Number of fins/inch	Not stated	Not stated	11	6
Number of tubes	Not stated	Not stated	130	Not stated
Core length (in.)	Not stated	21-15/16	19	23
Core width (in.)	Not stated	19-3/8	21	19%
Core thickness (in.)	Not stated	2-1/4	2.13/16	3
Water pump manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Thermostat manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Temp range (open & closed) °F	180 full open	160-180	212 full open	178-202
Fan belt manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Generator or alternator belt manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Engine lub. system-type cyl. lub.	Squirt & splash	Oil pump	Pressure	Sub. rotor pump
Type main bearing lub.	Pressure	Oil bath	Full pressure	Oil bath
Operating lb/in ² (a idle/max. rated speed	8/30-70	20/	40/60	35/60
Capacity (qt)	5	9	9	9
Oil filter manufacturer	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Type	Full flow	Full flow	Full flow	Full flow
Filtration range – micron	Not stated	Not stated	Not stated	Not stated
Battery manufacturer	Gould	General	Exide	Prestolite
Type	12-volt wet & chgd.	12-volt wet	12-volt	12-volt
Ground (positive or negative)	Negative	Negative	Negative	Negative
Battery capacity	60-amp	85-amp	70-amp	72-amp hr
Conform to SAE J537	Yes	No	Yes	Yes

18/5/Not stated Ford Motor Co. Ford Motor Co. Clark Model CT 40 Yes Not stated 37 @ 6500 Not stated Negative Suction Integral Delco Delco Delco 6500 Clark Yes Table 2. Comparison of Technical/Automotive Characteristics of Four Commercial Warehouse Tractors (Cont'd) 106 20 S. 9 20 17 5-v - 40 @ 2000 Huskie Model 40 Pettibone Model ord Motor Co. 17/5/Not stated Ford Motor Co. Ford Motor Co. Ford Motor Co. Ford Motor Co. Pulley-driven Elec solenoid Not stated Pettibone Negative Separate Suction ockoff 5500 Yes Se S 20 Shop Mule SM-40 17/3/Not stated United Model No – low lead Not stated United tractor Specifications, Power Train Not stated Not stated Chrysler Negative Chrysler Separate Chrysler Chrysler Chrysler Suction Yes S. S S. 20 13 Northwestern Model J6-40PT15 Northwestern Not stated Not stated Motorola Motorola Negative Integral 18/7/3% Chrysler Chrysler Chrysler Suction 1.325 Yes 2 9 14 r/min (a engine no-load governed speed Engine operate on lead-free gasoline Protection against reverse polarity Diameter/Number of blades/pitch Fuel consumption/hour (US gal) Voltage regulator manufacturer Location (integral or separate) Rated output - amps (a r/min Forque converter manufacturer Ground (positive or negative) Equipped with shut-off valve Starter motor manufacturer Hold-downs acid resistant Conform to ANSI B56.4 Specifications Type (suction; blower) Alternator manufacturer Fuel tank manufacturer Hold-downs furnished Capacity (US gal) an manufacturer Fungusproofing Waterproofing Viscous drive Size (in.)

154 @ 1660

1.12:1

1246

Not stated

Not stated

2140

Not stated Not stated

Not stated

Not stated

2.0:1 1740 10½

Eng. vac. at torque conv. stall speed - in. hg.

Oil type

Forque converter stall speed - r/min

Max. input torque – (lb/ft) @ r/min

Input torque rating (Ib/ft) (a r/min

Max. stall torque rated

1.86:1

Not stated

on of Technical/Automotive Characteristics of Four Commercial Warehouse Tractors (Cont'd)

Table 2. Comparison of Technical/Automotive Characteristics of Four Commercial materi	chnical/Automotive Characte	cristics of Four Commercia	that the same of t	
Specifications	Northwestern Model	United Model	Pettibone Model	Clark Model
- Specifications	J6-40PT15	Shop Mule SM-40	Huskie Model 40	C140
(SID :	Not stated	Not stated	Not stated	5.5
Oil capacity (US qt)	Chrysler	Chrysler	Ford Motor Co.	Ford Motor Co.
Transmission manufacturer	Ame	Auto	Auto.	Auto.
Type	Auto.	3-1	3.1	2-1
No. of speeds forward - reverse	3:1	9 at 16 pz.	4	5.5
Oil capacity (qt)	4.6/2	A 44 16 6	4	ш.
Oil type	A	Dadiator/tube & fin	Trans, mtd. radiator	Radiator lower
Type oil cooling	Kadiator liquid	Naulatol/tube ex iiii	cooled	tank
	2	Z	No	No
Transmission inching provided	00.		S. Z.	No
Transmission disconnect provided	ON	ONI		
Gear ratios speed (mi/h)	9 7 3 7 6	2 45-1-5 35	2.4-6.2	Blocked out
First	2.43-0.0	2001.596	2.0-7.6	2.00-6.5
Reverse	0.7-2.2	1 45 1.9 04	1.47-10.2	1.47-8.9
Second	2.11-6-1	1.00:13.10	10-15.2	1.00-13
Third	1.1-15.0	01:61:00:1	400 @ 3600	Not stated
Input torque rating (lb/ft) (a r/min	195 (a 2000	Not stated	Soor a cot	Not stated
Filter element manufacturer	Chrysler full flow	Chrysler	None	Not stated
Dhysical location	Bottom of sump	Valve body assy.	V/V	Not stated
Filyaction condo microns	Not stated	Not stated	Not stated	Not stated
FILITATION TAINES - microns	Mechanics universal	Mechanics universal	Mechanics universal	Spicer
Time (age 6 A F 1001)	2-ioint in-board	Not stated	Cardan	Cardan
Type (Iel. 3AL 3701)	2-joint Cardan	114-3100 3CL (type)	1-slip-type	1410
Universal joints (100. & type)	1950	1950	2445	250
l'orque capacity (10/11)	Rockwell Std.	Rockwell Std.	Rockwell Std.	Clark
Front axle manufacturer	S. S	ÖN	No	No
Driven	A/N	N Z	N/A	N/A
Type (drive-axie only)	None	Not stated	None	Not stated
Capacity rating: torque	3600	Not stated	2200	2500
Beam load (Ib)	Lonfenring	Leaf spring	Leaf spring	Leaf spring
Type of suspension	Rockwell Std	Rockwell Std.	Rockwell Std.	Clark
Kear axle manufacturer	Vae	Yes	Yes	Yes
Driven	531	beters toN	Diff, carrier, drop	Full floating
Type (drive-axle only)	Semi-noating	MOI Stated	box (SAE 1923)	
Gear reduction ratio	14.14:1	17:1	14.14:1	17.311:1
Ocal Icanacion iano				

Table 2. Comparison of Technical/Automotive Characteristics of Four Commercial Warehouse Tractors (Cont'd)

Specifications	Northwestern Model J6-40PT15	United Model Shop Mule SM40	Pettibone Model Huskie Model 40	Clark Model CT 40
Torone (lb ft)	Not stated	Not stated	365	0529
Boom Load (Ik)	Doi: 101	Deteta toN	7000	10.000
Dealii loau (10)	noi stated	lyol stated	0001	000.01
Type of suspension	Leaf spring	Spring-cushion pads	Leaf spring	Leaf spring
Front wheels manufacturer	DICO	Electric wheel	Geneva wheel	Rudd
Rim type	Drop center	Double disc	Split-S.D.C.	Disc halves
Tire size & ply ratings	8.00 x 10	6.00 x 10	6 x 00.9	6.50 x 10
	4-ply	6-ply	6-ply	6-ply
No. of tires per axle		2	2	2
Wheel loading (lb)	840	800	1000	950
Wheel loading w/rated load (lb)	840	387	006	500
Rear wheels manufacturer	Northwestern	Budd	Budd wheel	Budd
Rim type	Drop center	Rim w/side ring	Goodyear LTS	2-pe conv. rim
				drop cen.
Rim size	6.00 x 16.5	5.50 x 16	5.50 x 16	16. x 5.50 F
				6-hole
Tire size & ply rating	8.0 x 16.5	6.50 x 16	7.00 x 16	6.50 x 10
	6-ply	6-ply	6-ply	6-ply
No. of tires per axle	2	4	7	2
Wheel loading (lb)	1725	838	1880	1950
Wheel loading w/rated load (lb)	1725	1044	1980	2268
	Specifications,	Specifications, Steering & Brakes		
Steering system type	Manual	Manual	Manual	Manual
Steering control unit manufacturer	Saginaw	Ross	Ross	Saginaw
Power steering pump supplied	N/A	N/A	N/A	N/A
Pump manufacturer	N/A	N/A	N/A	N/A
Max. system pressure	N/A	N/A	N/A	N/A
Steering wheel dia (in.)	18	18	17	18
No. of turns lock-to-lock	5	51/2	5-2/3	5.3
Braking system manufacturer	Rockwell	Rockwell	Rockwell	Bendix
Front brakes	Drum	None	Drum	Drum
Lining	Bonded	None	Bonded (28 in.2)	Bonded
LxWxT(in.)	Not stated	None	$4 \times 1\% \times 3/16$	8 x 1.75 x Not
				stated

Specifications	Northwestern Model J6-40PT15	United Model Shop Mule SM40	Pettibone Model Huskie Model 40	Clark Model CT-40
Drum diameter (in.)	8	None	8	8
Type brake adjustment	Manual	None	Manual	Manual
Power assisted	No	None	Yes	Yes
Method of actuation	Hydraulic	None	Vacuum	Vacuum
Rear brakes	Drum	Drum	Drum	Drum
Lining	Bonded	Bonded	Bonded (63 in. ²)	Bonded
$L \times W \times T$ (in.)	Not stated	14 x 21/4 x 1/4	28 x 21/4 x 1/4	14 x 2 x Not stated
Drum dia (in.)	12%	121/2	121/4	14
Type brake adjustment	Manual	Manual	Self-adjusting	Manual
Power assisted	No	No	Yes	Yes
Method of actuation	Hydraulic	Hydraulic	Vacuum	Vacuum
Master brake valve manufacturer	Bendix	Wagner	Bendix	Bendix (dual split
				System)
Parking brake manufacturer	Chrysler	Chrysler	Ford Motor Co.	Orschelin
Type	Shoe	Shoe	Shoe	Friction band
Type of actuation	Lever	Lever	Lever Orschelin	Lever
Equipped with locking device	Yes	Yes	Yes	Yes
Location of brake	Transmission	Transmission	Transmission	Transmission
	Specifications, Ope	Specifications, Operator's Compartment		
Directional control				
Actuation	Right hand	Right hand	Right hand	Right hand
Location	Dash board	Beside driver	Beside driver	Beside driver
Position markings	Yes	Yes	Yes	Yes
Type	Embedded markings	Embossed	Metal decal	Screen decal
Seat				
Seat conform to SAE J899	Yes	Yes	No	Yes
Seat covered with vinyl or similar	Yes	Yes	Yes	Yes
Dimensions				
Distance between steering wheel and	10%		8%	7.0
seat (in.)				
Height of seat above floor (in.)	16	18	16	17.62
Height of floor above ground (in.)	26-14%	25	26-14	24.75
Distance between seat & parking brake (in.)	1	8	9	14.0

Specifications	Northwestern Model J6-40PT15	United Model Shop Mule SM-40	Pettibone Model Huskie Model 40	Clark Model CT-40
Distance between accl. & brake pedal (in.)	3	33/4	4	2.5
Dimensions of brake pedal (in.)	3½ W x 2½ H	3 in. dia.	3½ W x 2½ H	3 x 3
Location of pintle hook actuator	Rt. of opr. seat	On pintle hook	On rear counterweight	Rt. of opr. seat
	Specification	Specifications, Dimensional		
Overall length (in.)	101.5	66	101	102
Overall width (in.)	57	89	55	55.5
Overall height w/o cab (in.)	09	65	65	62.0
Wheel base (in.)	65	58	56.5	57.5
Drive tire tread width (C to C) (in.)	48	57.7	46	46.94
Steer tire tread width (C to C) (in.)	48	47	40.5	44.75
Clearance of drive tires to body (in.)	3	4.2	5	2.5
Minimum ground clearance (in.)	9	8.7	5.5	7.0
Height of exhaust outlet (in.)	9.75	9.5	10	7.25
Thickness of front bumper plate (in.)	0.5	0.5	0.5	0.5
Thickness of rear bumper plate (in.)	0.5	0.5	3.	0.5
Pintle hook height/vert. adj. (in.)	12/2	12/0	12/0	12/16
Gross vehicle weight (lb)	5300	5350	5450	6400
Ultimate DBP (lb)	4000	4000	4000	4000
Vehicle clearance circle (ft)	8.61	18.83	9.61	19.18
Travel speed – fwd (mi/h)	15.0	13.0	15.0	13.0
rev (mi/h)	7.0	6.5	7.5	6.5
Vehicle noise levels				
No load gov. eng. speed (dB(A))	82	95	82	. 85
At 4000 lb DBP (dB(A))	Not stated	72	Not stated	73

d. Each manufacturer complied with the request to list industrial users of the tow tractor described in the TIP. These users will be surveyed in a subsequent phase of this program.

IV. CONCLUSIONS

10. Conclusions. It is concluded that:

- a. Commercial warehouse tractors do not differ significantly from warehouse tractors previously procured by the Army using MIL-T-52852.
- b. The following makes and models of commercial warehouse tractors will be offered by the manufacturers to meet the Government's new specification: Clark CT-40, Northwestern J6-40-PT15, Pettibone Huskie Model 40, and United Shop Mule SM-40.
- c. Industrial users of the candidate makes/models of commercial ware-house tractors were identified.

APPENDIX

ITEM DESCRIPTION FOR TRACTOR, WHEELED, WAREHOUSE, GASOLINE, 4000-POUND-DRAWBAR-PULL, PNEUMATIC-TIRED

1. Scope. This description covers a commercial model warehouse tractor equipped with a gasoline engine; automatic transmission; two single, non-driving, steerable front wheels; two single, driving, non-steerable rear wheels; pneumatic tires; four-wheel-sprung suspension; and four-wheel-split-brake system. The warehouse tractor shall be the latest model of the standard commercial product of the supplier and shall have been in production, marketed, and in use in significant quantities by commercial or Federal Government users for a minimum of 1 year prior to the Step I technical proposal opening date. The introduction of normal product improvement changes in this 1-year period is acceptable.

2. Requirements.

- 2.1 General. The warehouse tractor shall be equipped with standard instruments, components, and accessories normally required for the safe and effective operation of the tractor. The tractor shall be complete with all components that are standard with the supplier's products, whether stipulated herein or not, together with such accessories as may be specified herein. The tractor shall be equipped with all other components and parts not specifically mentioned but necessary to provide a functional machine and shall conform in quality to that normally provided to the commercial industry.
- 2.2 Operating Temperature. The tractor shall start without preheating and shall be designed for operation in any ambient from 0°F to plus 110°F.
- **2.3 Safety.** The tractor shall conform to the requirements of ANSI B56.4, Type G.
- 2.4 Drawbar Pull. The tractor shall be capable of developing a towing force of not less than 4000 lb at a 12 plus or minus ½-inch coupler height on a level, clean, brushed, concrete surface.
- 2.5 Speed. The tractor, without trailing load, shall be capable of attaining a minimum of 12 miles per hour speed in high gear on a level surface.

- 2.6 Coupler. The tractor shall be equipped with a semi-automatic pintle-type coupler. The coupler shall consist of a coupler jaw configuration with a minimum throat opening of 1% inches and a minimum throat length of 5% inches and an accompanying spring-loaded laten and pin.
 - 2.7 Instruments. The tractor shall be furnished with the following instruments:
 - a. Hour meter.
 - b. Ammeter, voltmeter, or red alternator indicator light.
 - c. Fuel gauge.
 - d. Engine oil pressure gauge or warning light.
 - e. Engine coolant temperature gauge or warning light.
 - 2.8 Lights. The tractor shall be furnished with the following lights:
 - a. Two sealed-beam-type headlights.
 - b. One automotive, red, reflector-type, combination stop- and tail-light.
 - c. Backup light.

DISTRIBUTION FOR MERADCOM REPORT 2239

No. Copies	Addressee	No. Copies	Addressee
	Department of Defense	1	Chief, Engineer Division DCSLOG
12	Defense Documentation Center		ATTN: AFKC-LG-E
	Cameron Station		HQ Sixth US Army
	Alexandria, VA 22314		Presidio of San Francisco, CA 94129
1	Commander TARCOM'	1	Commander
	DRSTA-GBC	1	US Army Aberdeen Proving Ground
	Warren, MI 48090		ATTN: STEAP-MT-U
	wanten, wir 10070		(GE Branch)
1	Commander		Aberdeen Proving Ground, MD
	TARCOM		21005
	DRSTA-WS		
	Warren, MI 48090	1	Commander US Army Troop Support &
2	Commander		Aviation Materiel Readiness Com
	TARCOM		ATTN: DRSTS-KTE
	DRSTA-MUM Warren, MI 48090		4300 Goodfellow Blvd St Louis, MO 63120
	Warten, M1 48090		3t Eddis, MO 03120
2	Commander	1	HQ, USAREUR & Seventh Army
	TARCOM		DCSENGR, ATTN: AEAEN-MO
	DRSTA-QKC		ATTN: Mil Ops Div
	Warren, MI 48090		APO New York 09403
	Department of the Army	1	Commander USA DARCOM Installation and
1	Commander		Services Activity
	US Army Logistics Evaluation Agency		ATTN: DRCIS-RI
	DALO-LES		Rock Island, IL 61201
	New Cumberland Army Depot, New Cumberland, PA 17070	1	President
	New Cumberland, FA 17070		US Army Armor and Engineer Board
1	Commander, HQ TRADOC		ATTN: ATZK-AE-TD-E
	ATTN: ATEN-ME		Fort Knox, KY 40121
	Fort Monroe, VA 23651		
		1	Commander
1	Commander		OTEA
	Packaging Storage and		CSTE-POD
	Containerization Center DRXTO-T		5400 Columbia Pike Falls Church, VA 22091
	Tobyhanna Army Depot,		Talls Church, VA 22091
	Tobyhanna, PA 18966	2	GSAFSS
			Rm 1009CM4
2	Commander		(ATTN: Mr. Smith, Mr. McQuire)
	US Army Materiel Development and		Washington, DC 20406
	Readiness Com Ammunition Ctr		
	SARAC-DEV	1	Commander
	Savanna, IL 61704		HQ DLA
			ATTN: DLA-OW Cameron Station, VA
			Alexandria, VA 22314

No. Copies	Addressee	No. Copies	Addressee
1	Commander US Army Test & Evaluation Com ATTN: DRSTE-AR Aberdeen Proving Ground, MD 21005	l	MERADCOM Commander, DRDME-Z Technical Director, DRDME-ZT Assoc Tech Dir/R&D, DRDME-ZN
l	Commander US Army Materiel Development and Readiness Command ATTN: DRCDE-DS 5001 Eisenhower Avenue Alexandria, VA 22333	1	Assoc Tech Dir/Engrg & Acq, DRDME-ZE Spec Asst/Matl Asmt, DRDME-ZG Spec Asst/Tech Asmt, DRDME-ZK CIRCULATE Chief, Ctrmine Lab, DRDME-N
1	Commander US Army Maintenance Management Center ATTN: DRXMD-EV Lexington Bluegrass Army Depot Lexington, KY 40507	•	Chief, Engy & Wtr Res Lab, DRDME-G Chief, Elec Pwr Lab, DRDME-E Chief, Cam & Topo Lab, DRDME-R Chief, Mar & Br Lab, DRDME-M Chief, Ctr Intrus Lab, DRDME-X Chief, Matl Tech Lab, DRDME-V
1	Commandant US Army Quartermaster School ATTN: ATSM-CD-M Fort Lee, VA 23801	. 1	Director, Product A&T Directorate, DRDME-T CIRCULATE Mech & Constr Eq Lab, DRDME-H
1	Commander US Army Logistics Center ATTN: ATCL-ET Fort Lee, VA 23801	5 50 1	Mech Eq Engr Div, DRDME-HM Warehouse & Depot Grp, DRDME-HM Project Officer for Commercial Eqpt, DRDME-HC
1	Commandant US Army Transportation School ATTN: ATSP-CTD-MC Fort Eustis, VA 23604	3 3 2 1	Tech Reports Ofc, DRDME-WP Security Ofc (for liaison officers), DRDME-S Tech Library, DRDME-WC Plans, Programs & Ops Ofc,
1	AFLC CASO/LODS Federal Center Battle Creek, MI 49016	1	DRDME-U Pub Affairs Ofc, DRDME-I Ofc of Chief Counsel, DRDME-L
1	Commanding Officer Navy Ships Parts Control Center (Code 3456) Mechanicsburg, PA 17055		
1	Commander Defense Construction and Supply Ctr DCSC-SS Columbus, OH 43215		
1	Commandant of the Marine Corps HQ Marine Corp (Code LME – Mr. Zapf) Washington, DC 20380		